



The Jolt Rider product is intended to retrofit to existing seat locations, however ergonomic outcome may vary depending case by case. These dimensions are as a general guide only, please inquire directly for advice on your specific requirements.

The Jolt Rider product is intended to be mounted with 6x suitable M8 Stainless Steel 316 capscrews with applicable isolation washers or equivalent measures to counter Galvanic Corrosion.

The fasteners must have a thread engagement of no less than 16mm through the deck, equivalent reinforcing plate, or threaded inserts. Jolt Rider takes no responsibility for inadequate supporting deck structure, please refer to your local boat manufacturer, supplier or marine engineer.

	DIMENSIONS ARE IN: mm TOLERANCES: Angular: +/- 0.5 One Place Decimal: +/- 0.100 Two Place Decimal: +/- 0.050 Three Place Decimal: +/- 0.025		REVISION <b>A</b>	NOTES <b>ISSUED FOR REFERENCE</b>	DATE <b>20180920</b>	TITLE / PART NUMBER: <b>JOLTRIDER PRO JRP-1804 Customer Technical Drawing</b> Sheet1			
	MATERIAL: n/a VOLUME: n/amm <sup>3</sup>	FINISH: n/a DENSITY: n/ag/mm <sup>3</sup>	REVISION - -	NOTES - -	DATE - -	REVISION: <b>A</b>	SHEET: <b>1 OF 1</b>	SCALE: <b>1:20</b>	SIZE: <b>A3</b>
Copyright © 2018 Jolt Rider Ltd. Information contained in this drawing may not be reproduced or used for any purpose without express written permission from Jolt Rider Ltd. joltrider.com   sales@joltrider.com   PO Box 303222, North Harbour 0751, Auckland, New Zealand		WEIGHT: 26kg each		DRAWN BY: JOLT RIDER		APPROVED: n/a			